

REFERENCE	MODEL REFERENCE	CYE 224/G
PRESENTATION	PRODUCT DESCRIPTION	INOX / POLYCARBONATE
MODE D'ECLAIRAGE	SYSTEM MODE	FLUORESCENT
TYPE D'ECLAIRAGE	LIGHT TYPE	PERMANENT-MAINTENED
DOUILLE	SOCKET	G5
LAMPE SECOURS	EMERGENCY LAMP	2 x FLUO 24 WATTS T5
CLASSE DE PROTECTION	PROTECTION CLASS	2
TENSION D'ALIMENTATION	RATED VOLTAGE	230 V 50/60 HZ
CONSOMMATION	CONSUMPTION	0,17 A
BALLAST	BALLAST	ELECTRONIQUE
FLUX LUMINEUX	LIGHT FLUX	3300 LUMENS
MONTAGE	MOUNTING	MURAL
GRADUATION	GRADUATE	OUI
CABLAGE	CABLING	NON FLAMMABLE
COULEUR COFFRET	COLOUR CASE	INOX - TRANSPARENT
JOINT	GASKETS	NEOPRENE
FIXATION	MOUNTING	COLLIERS INOX VARIABLES
ENTREE DE CABLE	CABLE ENTRIES	PRESSE ETOUPE 13
NORMES	STANDARD	EN 60598 -1
REFLECTEUR	DIFFUSER	ALUMINIUM ANODISE
TENUE AU FEU	FIRE ENDURANCE	960° M2
DEGRE DE PROTECTION	PROTECTION CATEGORY	IP66 IK10
CYLINDRE	CYLINDER	DIAMETRE 100mm
DIMENSIONS	SIZE	625 x 125 x 100mm
POIDS	WEIGH	4,0 Kgs

01 47 88 31 31

