Evacuation lighting

the self-contained units will be of the SATI type for ceiling or wall mounting or wall recessed in accordance with the integration plan, with an assigned luminous flux of 45 lumens for 1H, from BEHAR Sécurité, STAR series type STAREL - (ref: 43474) or equivalent.



Depending on the zone, wall-mounted edge blocks from the same Star STARL series (ref: 43469) may be installed.



Low-height areas will be equipped with BEHAR Sécurité type Star STARR45 - (Ref: 74115) edge blocks with 80 mm high pictograms.





Depending on the zone, Star STARLP (ref: 43492) ceiling-mounted edge blocks can be installed.



In outdoor areas, waterproof (IP65) wall-mounted edge blocks from the same Star STARLET series (ref: 74386) may be installed.



In outdoor areas, waterproof ceiling-mounted edge blocks from the same Star STARLPET series (ref: 74391) can be installed.



All edge blocks are fitted with screen-printed pictograms on 10 mm thick transparent edges, mounted on epoxy-painted steel housings. Any color upon customer request.

All evacuation units are also available in Bi-function, BAEH or DBR.



Ambient lighting

BEHAR Sécurité, Star collection, STARAMB type (ref: 43493) or equivalent. With a rated output of 500 Lumens in non-permanent mode. The ambient unit will have the same dimensions as the evacuation model.





Evacuation lighting

The units will be of the LSC type for ceiling or wall mounting or recessed wall mounting in accordance with the integration plan, with an assigned luminous flux of 45 lumens, made by BEHAR Sécurité, STAR series type STAR1EL - (ref: 33375) or equivalent.



Depending on the zone, Star STAR1L (ref: 33373) wall-mounted edge blocks can be installed.



Low-height areas will be equipped with BEHAR Sécurité type Star STAR1R45 - (Ref: 74116) edge blocks with 80 mm high pictograms.





Depending on the zone, Star STAR1LP-type ceiling-mounted edge blocks (ref: on request) can be installed.



In noble outdoor areas (Terrace, Rooftop), waterproof (IP65) wall-mounted edge blocks from the same Star STAR1LET series (ref: 43495) can be installed.



In outdoor areas, watertight ceiling-mounted edge blocks from the same Star STAR1LPET series (ref: on request) can be installed.



All edge blocks are fitted with screen-printed pictograms on 10 mm thick transparent edges, mounted on epoxy-painted steel housings. Any color upon customer request.

All evacuation units are also available in Bi-function, BAEH or DBR.



Ambient lighting

BEHAR Sécurité, Star series, type STAR360SC (ref: 33377) or equivalent. With a rated flux of 500 Lumens in non permanent mode. The ambient unit will have the same dimensions as the evacuation model.



